

TECHNICAL DATA SHEET FOR

E33T5-H10T-LMD / E33T5-H10T-RMD

5 Tray Electric Convection Oven TOUCH SCREEN CONTROL
10 Tray Electric Holding Cabinet TOUCH SCREEN CONTROL

MODEL OPTIONS:

E33T5-H10T-LMD - Left hand door model

E33T5-H10T-RMD - Right hand door model

OVEN FEATURES

- 5 1/1 GN Gastronorm tray capacity
- 85mm tray spacing
- Compact 610mm width
- Touch Screen control
- Individual shelf timers
- Icon driven program menu
- Up to 5 cooking stages
- USB port for program/icon updating
- Moisture Injection mode (5 levels)
- 2 speed bi-directional reversing fan system
- 5.8kW heating power
- Safe-Touch vented side hinged door
- Slam shut door latch
- Pendulum operation door handle
- Vitreous enamel oven chamber
- Plug-in continuous oven door seal
- Dual halogen oven lamps
- 100% recyclable packaging

HOLDING CABINET FEATURES

- 10 1/1 GN tray capacity
- 74mm tray spacing
- Touch Screen Control
- Individual shelf timers
- Electronic temperature control
- Continuous door seal
- Low velocity circulation fan system
- 4 dia. 76mm castors with 2 front castors with wheel and swivel lock, 2 rigid rear castors
- 100% recyclable packaging

ACCESSORIES

- Optional 3M Cuno water filter kit complete with cartridge and connection fittings



Model E33T5-H10T-LMD

Model E33T5-H10T-RMD

E33T5-LMD E33T5-RMD

Unit shall be a Moffat electrically heated Turbofan convection oven. The oven shall have a one piece vitreous enamel oven chamber, stainless exterior top and sides. The oven shall have a vented safe touch side hinged door with slam shut latching and pendulum operation door handle. Oven shall have capacity for 5 half size sheet pans or 5 1/1 GN pans. The oven shall have selectable moisture level injection and a 2 speed oven fan. The oven shall be controlled by a 5.7" Touch Screen control with icon driven recipe programs and individual shelf control operation mode and multiple stage cooking. Oven controller shall have USB port for recipe file uploading and downloading. The oven shall include dual halogen oven lamps. Unit shall be supplied in 100% recyclable shipping packaging.

H10T-LMD H10T-RMD

Unit shall be a Moffat electrically heated Turbofan Holding Cabinet. The holding cabinet shall have double skin insulated construction with stainless steel interior and exterior sides, front and top. Door shall be side hinged. Unit shall have capacity for 10 half size sheet pans or 10 1/1 GN pans. A single speed fan shall gently and evenly circulate air around the cabinet. Cabinet shall be controlled by a 5.7" Touch Screen control with individual shelf timers and cabinet temperature control. Holding cabinet shall be mounted on castors, with two rigid castors at rear and two castors, swivel and wheel lock at front. Holding Cabinet shall be fitted with a plug-in cordset. Unit shall be supplied in 100% recyclable shipping packaging.

E33T5-LMD/RMD 1/1 GN Convection Oven Touch Screen Control H10T-LMD/RMD 1/1 GN Electric Holding Cabinet Touch Screen Control

CONSTRUCTION - OVEN (E33T5)

Vitreous enamel fully welded oven chamber
Stainless steel front, sides and top exterior
Stainless steel oven fan baffle and oven vent
Removable 5 position stainless steel side racks
Stainless steel frame side hinged door
5mm thick door outer glass
5mm thick low energy loss door inner glass
Stainless steel control panel
Aluminised coated steel base and rear panels

CONSTRUCTION - HOLDING CABINET (H10T)

Double skin insulated construction
304 stainless steel interior cabinet
Stainless steel front, sides and top exterior
Stainless steel interior side racks
Stainless steel frame, side hinged door
5mm thick door glass
Stainless steel control panel
Aluminised coated steel base and rear panels

CONTROLS (E33T5 Oven)

5.7" LED backlit touch screen
Icon driven program menu
BMP image icon imports via USB port
Program updates via USB port
Temperature range 30 - 260°C
Adjustable sounder tones and volume
Safety thermostat cut-out

CONTROLS (H10T Holding Cabinet)

5.7" LED backlit touch screen
Individual shelf timers
Temperature range 20 - 90°C

CLEANING

Stainless steel top and side exterior panels
Vitreous enamel oven chamber
Fully removable stainless steel oven side racks
Removable stainless steel oven fan baffle
Easy clean door system with hinge out door inner glass (no tools required)
Removable plug-in oven door seal (no tools required)

SPECIFICATIONS

Electrical Requirements

Oven (E33T5)
220V, 50Hz, 1P+N+E, 6.0kW, 27.3A
220V, 60Hz, 1P+N+E, 6.0kW, 27.3A
230-240V, 50Hz, 1P+N+E, 6.0kW, 25A
230-240V, 60Hz, 1P+N+E, 6.0kW, 25A
No cordset supplied

Holding Cabinet (H10T)

220V-240V, 50Hz, 1+P+N+E, 1.3kW, 5.4A
220V-240V, 60Hz, 1+P+N+E, 1.3kW, 5.4A
Cordset fitted

Water Requirements (Oven - optional)

Cold water connection 3/4" BSP male
550kpa maximum inlet pressure / 150kpa minimum inlet pressure

External Dimensions (E33T5 / H10T)

Width 610mm
Height 1663mm
Depth 680mm

Nett Weight

148kg

Packing Data

214kg
Width 645mm
Height 1880mm
Depth 850mm
Volume 1.03m³

INSTALLATION CLEARANCES

E33T5-H10-LMD	E33T5-H10-RMD
Rear 50mm	Rear 50mm
LH Side 50mm	LH Side 75mm*
RH Side 75mm*	RH Side 50mm

* For fixed installations a minimum of 500mm is required for service

CLEARANCE FROM OPEN SOURCES OF HEAT

A minimum distance of 300mm from the appliance sides is required



Australia
www.moffat.com.au
New Zealand
www.moffat.co.nz
www.turbofanoven.com

Australia
Moffat Pty Limited

740 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Facsimile 03-9518 3833
nsw@moffat.com.au

New Zealand
Moffat Limited

16 Osborne Street
Christchurch 8011
Telephone 03-389 1007
Facsimile 03-389 1276
sales@moffat.co.nz



Designed and manufactured by
MOFFAT

ISO9001

All Turbofan products are designed and manufactured by Moffat using the internationally recognised ISO9001 quality management system, covering design, manufacture and final inspection, ensuring consistent high quality at all times.

In line with policy to continually develop and improve its products, Moffat Limited reserves the right to change specifications and design without notice.

