

# metos

## Viking and Viking Combi

STATIC & COMBI JACKETED KETTLES



**MOFFAT**

# VIKING STATIC JACKETED KETTLES

Viking static jacketed kettles are efficient and user friendly basic kettles for almost all types of professional kitchens. Thanks to the large steam jacket that extends to the kettle's upper rim, soups, sauces and many other products will be cooked faster. Electrical tilting makes unloading easy. Multiple Viking kettles can be installed in line which saves space in a kitchen.

- All stainless steel construction, inner bowl of acid proof steel
- Stepless temperature control, maximum +120 °C
- Maximum working pressure in steam jacket 1,0 bar
- Electrical tilting

#### STANDARD EQUIPMENT:

- Removable lid (150-400 litre with hinged lid)
- Water faucet (cold water)
- Volume measurement stick
- Hook for accessories on left and right pillar (single kettle)
- Hand shower hose
- Strainer plate



A hinged lid is standard in 150-400 litre Viking kettles and available as an option in smaller kettles.

## JOM PUMPING SYSTEM

JOM Hot-fill DOS 2 ensures quick and precise dispensing of liquid food products. Soups, sauces and mashed potatoes are filled into bags and containers effortlessly.

**Compatible with Viking and Viking Combi Kettles.**



Please contact Moffat Pty Ltd for more information on this JOM Pumping System.

# VIKING COMBI JACKETED KETTLES

Viking combi jacketed kettles are a basic cooking kettle with powerful integrated mixing device for versatile and professional food production. With the use of the integrated mixer, many dishes can be cooked from start to the finish in one unit, without any food transfer. Mixing assists heat transfer and food is cooked faster and more evenly. Labour intensive manual mixing is a thing of a past. Unique mixing features enable, for example, crushing of minced meat and mashing of potatoes for purées.

- All stainless steel construction, inner bowl of acid proof steel
- Stepless temperature control, maximum +120 °C
- Maximum working pressure in steam jacket 1,0 bar
- Electrical tilting
- Integrated mixer: stepless mixing speed control (20-110 rpm), two mixing programs (gentle mixing, hard mixing)
- Autoreverse mixing
- Mixing tool with removable scrapers

#### STANDARD EQUIPMENT:

- Hinged removable safety grid lid
- Water faucet (cold water)
- Volume measurement stick
- Hook for accessories on left and right pillar (single kettle)
- Hand shower hose
- Strainer plate

The Viking kettles can be combined with the Culino and Proveno kettles for efficient and versatile high capacity kettle groups.



Viking combi kettles are supplied with safety grid lid as standard.



**ELECTRIC**

Viking	Dimensions (mm)	Electric Connection
Viking 40E	1047 x 743 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 16A, 9kW
Viking 60E	1047 x 743 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 20A, 10.5kW
Viking 80E	1154 x 792 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 20A, 12kW
Viking 100E	1154 x 792 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 25A, 16kW
Viking 150E	1360 x 965 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 32A, 20kW
Viking 200E	1360 x 965 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 50A, 30kW
Viking 300E	1560 x 1161 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 60A, 40kW
Viking 400E	1560 x 1161 x 1198	3 Phase+N+E, 400-415V, 50/60Hz, 100A, 57.6kW



Viking Combi	Dimensions (mm)	Electric Connection
Viking Combi 40E	1047 x 743 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 25A, 9.75kW
Viking Combi 60E	1047 x 743 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 25A, 11.25kW
Viking Combi 80E	1154 x 792 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 32A, 12.75kW
Viking Combi 100E	1154 x 792 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 35A, 16.75kW
Viking Combi 150E	1360 x 965 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 50A, 21.5kW
Viking Combi 200E	1360 x 965 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 63A, 31.5kW
Viking Combi 300E	1560 x 1161 x 1039	3 Phase+N+E, 400-415V, 50/60Hz, 80A, 41.5kW
Viking Combi 400E	1560 x 1161 x 1198	3 Phase+N+E, 400-415V, 50/60Hz, 100A, 59.8kW

**FACTORY ORDER OPTIONS:**

- Hinged lid Viking (40-100L)
- Cooling C1
- Draw off spigot D1-std
- Draw off valve connection D2-B
- HACCP facilities
- HACCP connection package
- Evaporation lid

**OPTIONAL:**


- Strainer plate extension 300-400
- Pouring adapter
- Whipping grid

**STEAM**

Viking	Dimensions (mm)	Electric Connection	Steam Cons.
Viking 40S	1047 x 890 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.3kW	12 kg/hr
Viking 60S	1047 x 890 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.3kW	18 kg/hr
Viking 80S	1154 x 950 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.3kW	24 kg/hr
Viking 100S	1154 x 950 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.3kW	30 kg/hr
Viking 150S	1360 x 965 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.3kW	45 kg/hr
Viking 200S	1360 x 965 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.3kW	60 kg/hr
Viking 300S	1560 x 1161 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.5kW	90 kg/hr
Viking 400S	1560 x 1161 x 1198	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 0.5kW	120 kg/hr



Viking Combi	Dimensions (mm)	Electric Connection	Steam Cons.
Viking Combi 40S	1047 x 890 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 1.0kW	12 kg/hr
Viking Combi 60S	1047 x 890 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 1.0kW	18 kg/hr
Viking Combi 80S	1154 x 950 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 1.0kW	24 kg/hr
Viking Combi 100S	1154 x 950 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 1.0kW	30 kg/hr
Viking Combi 150S	1360 x 965 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 1.8kW	45 kg/hr
Viking Combi 200S	1360 x 965 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 1.8kW	60 kg/hr
Viking Combi 300S	1560 x 1161 x 1039	1 Phase+N+E, 230-240V, 50/60Hz, 10A, 2.0kW	90 kg/hr
Viking Combi 400S	1560 x 1161 x 1198	1 Phase+N+E, 230-240V, 50/60Hz, 15A, 2.7kW	120 kg/hr



**Installation frames**

Please see the price list for instructions.

**Australia  
Moffat Pty Limited**

**Victoria / Tasmania**  
740 Springvale Road  
Mulgrave VIC 3170

Phone 03 9518 3888  
Fax 03 9518 3833  
Email vsales@moffat.com.au

**New South Wales**  
Phone 02 8833 4111  
Email nswsales@moffat.com.au

**South Australia**  
Phone 03 9518 3888  
Email vsales@moffat.com.au

**Queensland**  
Phone 07 3630 8600  
Email qldsales@moffat.com.au

**Western Australia**  
Phone 08 9202 6820  
Email bgarcia@moffat.com.au

**New Zealand  
Moffat Limited**

**Rolleston**  
45 Illinois Drive, Izone Business  
Hub  
Rolleston 7675  
Phone +64 3 983 6600  
Fax +64 3 983 6660  
Email sales@moffat.co.nz

**Auckland**  
Phone +64 9 574 3150  
Email sales@moffat.co.nz



www.moffat.com.au  
www.moffat.co.nz

©Copyright Moffat Pty Limited  
Moffat 10.15

